

## Professional Manufacturer of Optical System

## **Pomeas Macro Lens Series**

## **PMS-07ML100**

- 1. Support 3MP camera or below
- 2. High resolution super low distortion even illumination image.
- 3.Support 2/3" Sensor
- 4.Standard C-Mount

Max.Sensor Size 2/3"

Magnification 0.7X

Working Distance 100mm Resolution 6.71µm


C-Mount



Code		PMS-07ML100				
Magnification		0.7X				
Field of View	1/4''	4.6mm×3.4mm				
	1/3''	6.9mm×5.1mm				
	1/2.5"	8.2mm×6.2mm				
	1/2.3"	8.8mm×6.6mm				
	1/2"	9.1mm×6.9mm				
	1/1.8''	10.2mm×7.7mm				
	2/3''	12.6mm×9.4mm				
Working Distance		100mm				
Resolution		6.71µm				
F.No.		7.1				
TV Distortion		0.02%				
Depth of Field*1		1.14mm				
N.A.		0.05				
Max.Sensor Size		2/3"				
Mount		C-Mount				
Illumination		<b></b>				
Working Temperature		-10°C ~ +50°C				

 $<sup>^{\</sup>star} 1: Theoretical\ calculating\ value (based\ on\ diameter\ of\ defocused\ spots\ is\ 0.04mm), in\ the\ reality\ application,\ take\ its\ 1/2\ will\ gain\ the\ best\ effect.$ 

www.pomeas.com



			Ø28 1−32T				
		<b> </b> → <u> </u>				<u></u>	C-MOUNT/17,53
1/0=186,8±3	69,22	56,72					نا
	W,D,=100±3			Ø:	.6 .		